

## PUMP ACCESSORIES

### GARDEN PUMP PRE FILTER 100/1"



110157

- | This pre-filter protects the interior of your Transfer water pumps against damage caused by dirt.

(Replacement filter element for pre filter 100/1" - 110166)

### DOMESTIC WATER SYSTEM PRE FILTER 250/1"



110156

- | This pre-filter protects the interior of your Household Water Supply pumps against damage caused by dirt.

(Replacement filter element for pre filter 250/1" - 110165)

### 7M SUCTION HOSE (1" DIAMETER)



110795

- | High quality suction hose complete with suction strainer, brass non-return valve and connectors.

### 4M SUCTION HOSE (3/4" DIAMETER)



110005

- | Includes a non-return valve integrated in the suction strainer

### 25MM NON-RETURN VALVE



110648

- | A required accessory when installing all HW pumps and some Jet pumps. Allows the water to flow in a single direction only, maintaining pressure in line or pressure tank.

## PUMP APPLICATIONS

### SUBMERSIBLE



Our submersible pumps are designed for all kinds of "underwater" applications, whether it be clean or highly contaminated and dirty water.

- | Removes water from a pond, stream or reservoir
- | Pumps out your swimming pool or water tank
- | Transfers water from one container to another
- | Effectively drain out basements flooded with water

### TRANSFER



Our range of transfer pumps are designed to assist with general water transfer.

- | Provides irrigation water for gardens and lawns from water tanks and other clean water supplies
- | Pumps clean water over long distances with high pressure
- | Tank water transfer/household supply

### HOUSEHOLD



Our domestic water systems are just the solution, they pump water automatically and at a constant pressure.

- | Provides a low-cost household water supply from your water tank or alternate clean water source
- | Increases pressure in your household water supply
- | Water gardens easily and effectively

### PETROL



Powerful pumps for the supply and transfer of large quantities of water in a very short time without the need for power supply.


- | High volume water removal or transfer
- | Irrigating the garden
- | Building site flooding
- | Fuel efficient 4 stroke engines

## ABOUT US

For more than 50 years, AL-KO has been developing and designing innovative tools for an extremely wide range of requirements and applications. Not only do AL-KO tools reflect its many years of expertise in technology and function, they also set new standards in terms of design.

The rigorous quality requirement that characterises the AL-KO brand is guaranteed through its comprehensive technology programme that is consistently planned and implemented by AL-KO development engineers, designers and technicians - from the first design, to prototype construction and the end product.

Why not take the plunge into the world of AL-KO and get to know its high-quality products - without doubt you will find just the right solution for your requirements.



Years Warranty

\*All electric pumps come with a 3 year warranty and petrol pumps come with a 2 year warranty

# Masport®

Distributed by: Masport New Zealand Limited  
1-37 Mt Wellington Highway Panmure, Auckland 1741  
P: 0800 627 7678 F: 0508 570 570 E: sales@masport.com

Distributed by: Masport Australia Pty Limited  
PO Box 533, Braeside, Victoria 3195  
P: 1300 366 225 F: 1800 035 594 E: csau@masport.com.au

**AL-KO**  
QUALITY FOR LIFE

## WATER PUMP RANGE 2019/20



## SUBMERSIBLE PUMPS

### SUB 6500 CLASSIC

112820-45

Robust submersible pump for shifting clean water at a flow rate up to 6500 l/h.



<b>Motor / power</b>	250 watts
<b>Cable length</b>	10m
<b>Max. lift/head</b>	6m
<b>Max. flow rate</b>	6500 l/h
<b>Max. submersible depth</b>	5m
<b>Pump output diameter</b>	G 1 1/4" (41.9 mm)

### DRAIN 7500 CLASSIC

112822-45

This is a very versatile submersible pump that pumps clean and/or dirty water and can manage particles as large as 30mm in suspension.



<b>Motor / power</b>	450 watts
<b>Cable length</b>	10m
<b>Max. lift/head</b>	6m
<b>Max. flow rate</b>	7500 l/h
<b>Max. submersible depth</b>	5m
<b>Max. particulate size</b>	30mm
<b>Pump output diameter</b>	G 1 1/4" (41.9 mm)

### DRAIN 12000 COMFORT

112826-45

Extremely strong and robust submersible clean and/or dirty water pump with a massive 850 watt motor and a maximum flow rate up to 12,000 l/h.



<b>Motor / power</b>	850 watts
<b>Cable length</b>	10m
<b>Max. lift/head</b>	10m
<b>Max. flow rate</b>	12,000 l/h
<b>Max. submersible depth</b>	5m
<b>Max. particulate size</b>	30mm
<b>Pump output diameter</b>	G 1 1/4" (41.9 mm)

## TRANSFER AND GARDEN PUMPS

### JET 3500 CLASSIC

112839-45

AL-KO's Jet 3500 Classic water pump draws in the water within the shortest possible time thanks to the built-in Single Stage Jet system. Flow rates up to 3400 l/h.



<b>Motor / power</b>	850 watts
<b>Max. lift/head</b>	38m
<b>Max. flow rate</b>	3400 l/h
<b>Max. Suction Height</b>	8m
<b>Suction/Pressure Hose Diameter</b>	G 1" (33.3 mm)
<b>Pump Hydraulics</b>	1-stage

### JET 5000 COMFORT

112842-45

AL-KO's Jet 5000 Comfort water pump has a powerful 1300 watt motor. This Jet pump comes with the Flow Control System (FCS) and an integrated XXL filter for optimum protection against contamination.



<b>Motor / power</b>	1300 watts
<b>Max. lift/head</b>	50m
<b>Max. flow rate</b>	4500 l/h
<b>Max. Suction Height</b>	8m
<b>Suction/Pressure Hose Diameter</b>	G 1" (33.3 mm)
<b>Pump Hydraulics</b>	1-stage

### HYDROCONTROL

112478-45



The Hydrocontrol automatically converts your existing transfer pump into a household water supply pump. It is easily fitted to any Jet pump with a 1" thread and will switch the pump on and off as you turn your tap on and off. Additionally, the Hydrocontrol will check pressure lines for leaks and has dry run protection should the water supply run out.

## HOUSEHOLD WATER SUPPLY PUMPS

### HW 3500 CLASSIC

112847-45

Suitable for pumping clean domestic water. Flow rates up to 3400 l/h



<b>Motor / power</b>	850 watts
<b>Max. lift/head</b>	38m
<b>Max. Suction Height</b>	8m
<b>Max. Head/Pressure</b>	38m / 3.8 bar
<b>Suction/Pressure Hose Diameter</b>	G 1" (33.3 mm)
<b>Pressure Tank Capacity</b>	17l
<b>Pump Hydraulics</b>	1-stage
<b>Switch On/Off Pressure</b>	1.5 bar / 2.8 bar

### HW 4500 FCS COMFORT

112850-45

Large high-powered pump suitable for clean domestic water. Flow rates up to 4500 l/h. Includes easy to clean XXL filter and Flow Control System (FCS).



<b>Motor / power</b>	1300 watts
<b>Max. Suction Height</b>	8m
<b>Max. Head/Pressure</b>	50m / 5.0 bar
<b>Suction/Pressure Hose Diameter</b>	G 1" (33.3 mm)
<b>Pressure Tank Capacity</b>	17l
<b>Pump Hydraulics</b>	1-stage
<b>Switch On/Off Pressure</b>	2.0 bar / 3.8 bar

### HWA 4500

113228-45

High powered compact pump with a integrated hydrocontrol pressure switch suitable for use with clean water. Flow rates up to 4500 l/h. Includes easy to clean XXL filter and Flow Control System (FCS).



<b>Motor / power</b>	1300 watts
<b>Max. Suction Height</b>	8m
<b>Max. Head/Pressure</b>	50m / 5.0 bar
<b>Suction/Pressure Hose Diameter</b>	G 1" (33.3 mm)
<b>Pump Hydraulics</b>	1-stage
<b>Switch Off Pressure</b>	5.0 bar

## PETROL WATER PUMPS

### BMP 30000

113563

The BMP 30000 has a feed/flow rate of up to 30,000 litres per hour with a maximum suction height of 6 metres. It's the perfect solution when you need to pump high volumes of water. The OHV AL-KO 4 stroke engine is powerful, very economical and its large fuel tank maximises long runtimes. Suction filter cage and connector included.



<b>Motor / power</b>	196cc 4.1 kW (5.5hp) / 3600 rpm
<b>Max. lift/head</b>	27m
<b>Max. flow rate</b>	30,000 l/h
<b>Max. Suction Height</b>	6m
<b>Pump input diameter</b>	G 2"
<b>Pump output diameter</b>	G 2"
<b>Fuel tank capacity</b>	3.6l

### BMP 14000

113562

Flow independent, petrol driven pump. Powerful and easy to start. Suction filter cage and connector included. Flow rates up to 14,000 l/h with a maximum suction height of 6 metres. This 4 stroke engine and pump only weighs 13kg which makes it easy to transport.



<b>Motor / power</b>	97cc 1.2 kW (1.6hp) / 3600 rpm
<b>Max. lift/head</b>	36m
<b>Max. flow rate</b>	14,000 l/h
<b>Max. Suction Height</b>	6m
<b>Pump input diameter</b>	G 1"
<b>Pump output diameter</b>	G 1"
<b>Fuel tank capacity</b>	1.4l